

JARVIS

Android POS Tablet for Retail



10 point
capacitive touch



STAROS
- kiosk lockdown app included

Starcontrol

STAR CONTROL
- remotely manager tablets



Commercial grade

Product overview

Glory Star Instore POS Tablets are designed for brands and retail shops to display interactive contents. STAROS the kiosk lockdown app is included in the tablet where it securely locks down the tablet from third party access, and with STARCONTROL, you can remotely manage the status of the tablets.

Available in 10", 14", 18.5", 23.8", 27", 31.5" widescreen high-performance CPUs and HD IPS capacitive touchscreens

Choice of Wi-Fi / Ethernet

Optimize deployments with cloud-based configuration, monitoring and scheduling

Modern design with flexible mounting in portrait, landscape and table-top orientation

Instore POS tablet

Specification		JAR101	JAR141	JAR185	JAR238	JAR271	JAR321
Screen size		10"	14 "	18.5"	23.8"	27"	32"
Panel info.	Resolution	1280 x 800	1920 x 1080	1366 x 768	1920 x 1080		
	Brightness	350 cd/m2	250 cd/m2	200 cd/m2	250 cd/m2	250 cd/m2	280 cd/m2
	Contrast	800:1	700:1	1000:1	1000:1	1000:1	1200:1
	Aspect Ratio	16:10	16:9				
	Active Display Area	134.8x216.2	165.4x294.3	228.0x407.7	294.4x522	337.1x598.6	393.8x699.4
	Viewing angle	H170°/ V170°	H178°/ V178°	H178°/ V178°	H178° / V178°	H170° / V 170°	H178° / V178°
	Touch Tech.	5point cap touch (6H semi-tempered glass)	10-point cap touch (6H semi-tempered glass)				
	Hardware & OS	CPU	RK3128 CortexA7, Quad core 1.2 GHz	RK3288 Cortex A17, Quad core 1.8 GHz			
RAM		1GB DDR3	2GB DDR3				
ROM		8GB eMMC Flash					
OS		Android 7.1					
Video/ Image	Video format	H.265, VP8, RV, WMV, AVS, H.263, MPEG4, HTML5, Flash 10					
	Audio format	MP3/ WMA/ AAC etc.					
	Image format	JPEG, BMP, PNG					
Audio	Speaker	2 x 1W	2 x 3W	2 x 3W	2 x1.5W	2 x 5W	2 x 5W
Communication	Bluetooth	EDR 4.0					
	Wi-Fi	802.11 b/g/n	802.11 b/g/n 2.4GHz and 5GHz				
	Ethernet	10/100 LAN					
General information	Color	Black					
	I/O	RJ45 x 1;USB x 3; SD slot x 1; Micro-USB x 1; 3.5mm audio x 1; Recover x 1					
	POE	Yes	N/A				
	Included in Box	Instore POS series tablet, Power Adaptor, Power cable					
	Sensors	G-sensor					
	Power input	12V 2A	12V 5A				
	Operating Environment	Operating: 32°F to 104°F (0°C to 40°C); Storage: -4°F to 122°F (-20°C to 50°C) Operating: 20%-80%; Storage: 10%-95%					
	Certification	CE, FCC, ROHS					
	Language	Multi language					
	VESA	VESA 75	VESA 75/100				
Dimension	Dimension (L x W x H)	250 × 28 ×172 mm	355 × 32.6 ×228 mm	462 × 37.5 ×282.5 mm	595.5 × 43.6 ×363.1 mm	662.73 × 60.53 ×400 mm	763.77 × 72.52 ×457.21 mm
	Weight	660g	1120g	2563g	4800g	5300g	8000g
	Box size/each PCs (L x W x H)	385 x 65 x222 mm	435 x 96 x320 mm	542 x 102 x375 mm	655x115 x455mm	725x115 x490mm	842x115 x575mm
	Master Box size (L x W x H)	470x400 x355 mm	443x396 x374 mm	550x318 x414 mm	670x250 x480mm	740x250 x515mm	864x258 x611cm
	Master Box weight	13.7Kg	8.76Kg	11.82 Kg	14.2Kg	15.6Kg	21.8Kg
	Pieces/Carton	10 PCS	4 PCS	3 PCS	2PCS	2PCS	2PCS

STAROS Features

STAROS	<ul style="list-style-type: none">• Kiosk lockdown• Set timer to turn device on and off	<ul style="list-style-type: none">• App Lockdown• Hide control buttons
STAR CONTROL	<ul style="list-style-type: none">• Manage device remotely• Upload video to device	<ul style="list-style-type: none">• Control power on/off• Manage apps remotely

To find out more about our extensive range of Glorystar solutions, go to www.glorystargroup.com , or call the office nearest you. For more information, please contact us at sales@glorystargroup.com. Glorystar reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. Glorystar, the Glorystar logo, STAR CONTROL and STAROS are either trademarks or registered trademarks of Glorystar Group Limited. All other trademarks are the property of their respective owners.